



# 5 IN 1 Slim Panel LED Recessed Downlight

Amico 6 Inch LED Emergency Recessed Lights with 90 Min Battery Backup 5 color temperature selectable, no need to worry about what color temperature to buy. Ultra-thin canless downlights only require as small as 6 inches ceiling spaces, fitting various ceilings, and joists. 1100LM consumes 16 Watts equivalent to 110W halogen lamp, saving you up to 90% in energy costs. 5-Year Warranty! We will be 100% responsible for our products!



## LIGHT DISTRIBUTION ANGLE



Chromaticity CIE1931 Diagram

## SPECIFICATIONS

Input Voltage	100~277V	Efficiency(LM/W)	68Lm/W
Max output Voltage	36V	Frequency	60Hz
Wattage	16W	Operating Temperature	-4°F-104°F
Input Current	0.13A	Suitable for Damp Locations Ingress	Yes
Max output Current	360mA	IC Rated	Yes
Power Factor	> 0.9	Housing	Metal
Lumens	1100LM	Wiring	Copper
Equivalency	110W	Average Life (Hours)	50000hours
Color Temperature	2700K/3000K/3500K/4000K/5000K	Warranty	5-Years
CRI	80+	Switching Time	> 30000
Beam Angle	120°	Emergency Lighting	≥90min
Dimmable	Yes		